



# A2O Pure



## Pure water nothing else

Experience an under-the-sink water purifier powered by Aquaporin's unique purification technology. The features provide clean water bursting with a drop of natural flavor.

The new, stylish and simplistic A2O Pure dispenses purified, great-tasting clean water directly from the tap. In addition, the A2O Pure-system offers the best possible safety by providing the highest removal rates for water contaminants. Furthermore, it measures the quality of your water, has leak detection, automatic cleaning, and a space-saving design.

The space matt-white front is perfect for anyone who favors style and simplicity. The A2O Pure embodies the Scandinavian minimalistic concept of appliances and offers a space to live, feel, and experience purified water.

The A2O Pure is the water purifier that secures one of life's most important assets, your and your family's health.



## A2O Pure Tankless RO System

Model name	A2O Pure
Product category	Under-the-sink

### Input water requirements

Feedwater temperature (min. / max.)	5–25°C
Inlet pressure (min. / max.)	1–6 bar
Feedwater quality	Municipal tap water

### Replacement filters

Name	Material	Lifetime
Pre filter	PP cotton + Activated carbon	12 months or 4,500 L
Post filter	Activated carbon	12 months or 4,500 L
DWRO®	Aquaporin Inside® membrane	24 months or 7,000 L

<sup>1</sup>The flow rate is tested at 25 °C; lower water temperatures will reduce the flow rate.

<sup>2</sup> The system is influenced by feedwater conditions such as pressure, temperature, TDS levels, and hardness. The better these incoming conditions, the better the performance. Depending on the local water quality and use environment, the lifetime of the filters, flow rate, recovery rate and salt rejection will vary.

<sup>3</sup> Local variations apply, contact your reseller for more information.

## Technical data

Flow rate of filtered water <sup>1</sup>	2.1 L/min
Water recovery rate <sup>2</sup>	65% (2:1)
Membrane capacity	126 L/h
Salt rejection <sup>2</sup>	> 90%
Electrical connection	220–240V AC
Power consumption (operation)	95 W
Power plug standard	EU
Noise level	53 ±1 dB
Wi-Fi connection + app	Yes
Leak detector	Yes
Membrane flushing (auto-cleaning)	Yes
Feed, pure, and wastewater connection	½ or ¾", ¼, ¼ inch
Dimensions (W×D×H)	315 × 203 × 427 mm
Weight	8.57 kg
Regulatory information	EUFCM and 